

Data Sheet

04/04

Oil Mist Separator Type 1.500/980

Housing	Mild steel, fully galvanized, outside painted, Internal parts aluminium, no brass or copper
----------------	--

Main dimensions	Diameter	400 mm
	Filter housing length	765 mm
	Pillar tube	300 mm
	Blower	422 mm
	Total height	1.487 mm
	Inlet flange	DN 100 PN 16, DIN2633
	Exhaust	2" tube

Weight	80 kg
---------------	-------

Filter elements	Glass fibre fleece with inorganic binder		
	Quantity	9 off	
	Dimension	length	476 mm
		diameter	51 mm i. d.
		wall thickness	6 mm
Filtration degree	0,1 μ		

Blower	Motor	1,1 kW 230/400 V, 50 Hz
	Protection	IP 55
	Sound Pressure Level	70 dB(A) at 50 Hz
	Flow	180 Nm ³ /h at 60 mbar Δ p
		205 Nm ³ /h at 20 mbar Δ p

Scope of supply	The CONTEC -oil mist separator units are supplied fully assembled and ready for installation including one set of filter elements, negative pressure gauge, hand ball valve for negative pressure control, air-suction-filter and 5 m of transparent oil return hose.
------------------------	--

GENERAL ARRANGEMENT OIL MIST SEPARATOR TYPE 1.500/980

