

Data Sheet

04/04

Oil Mist Separator Type 2.200/630

Housing	Mild steel, fully galvanised, outside painted, Internal parts aluminium, no brass or copper
----------------	--

Main dimensions	Diameter	400 mm
	Filter housing length	765 mm
	Pillar tube	300 mm
	Blower	435 mm
	Total height	1.500 mm
	Inlet flange	DN 100 PN 16, DIN 2633
	Exhaust	2" tube

Weight	90 kg
---------------	-------

Filter elements	Glass fibre fleece with inorganic binder and end caps		
	Quantity		9 off
	Dimension	length	540 mm
		diameter	63 mm i. d.
		wall thickness	6 mm
Filtration degree		0,1 μ	

Blower	Motor	2,2 kW 230/400V, 50 Hz
	Protection	IP 55
	Sound Pressure Level	71 dB(A) at 50 Hz
	Blower-Flow rate	273 Nm ³ /h at 60 mbar Δ p
		290 Nm ³ /h at 20 mbar Δ p

Scope of supply	The CONTEC -oil mist separator units are supplied fully assembled and ready for installation including one set of filter elements, negative pressure gauge, hand ball valve for negative pressure control, air-suction-filter and 5 m of transparent oil return hose.
------------------------	--

GENERAL ARRANGEMENT OIL MIST SEPARATOR TYPE 2.200/630

