

Data Sheet

04/04

Oil Mist Separator Type 2.200/630-SG

Housing	Mild steel, fully galvanised, outside painted, Internal parts aluminium, no brass or copper
----------------	--

Main dimensions	Filter housing	400 mm Ø
	Filter housing length	900 mm
	Pillar tube	400 mm
	Total width	700 mm
	Total height	1.300 mm
	Inlet flange	DN 100 PN 16, DIN 2633
	Exhaust	2" tube

Weight	100 kg
---------------	--------

Filter elements	Glass fibre fleece with inorganic binder and end caps		
	Quantity	9 off	
	Dimension	length	540 mm
		diameter	63 mm i. d.
		wall thickness	6 mm
Filtration degree	0,1µ		

Blower	Motor	2,2 kW 230/400V, 50 Hz
	Protection	IP 55
	Sound Pressure Level	71 dB(A) at 50 Hz
	Blower-Flow rate	273 Nm ³ /h at 60 mbar Δp
		290 Nm ³ /h at 20 mbar Δp

Scope of supply	The CONTEC -oil mist separator units are supplied fully assembled and ready for installation including one set of filter elements, negative pressure gauge, hand ball valve for negative pressure control, air-suction-filter and 5 m of transparent oil return hose.
------------------------	--

GENERAL ARRANGEMENT OIL MIST SEPARATOR TYPE 2.200/630-SG

