

Side entry float switches

The **Side Entry** series of single point float switches are manufactured in a range of materials to suit varied applications.

Most switches are mounted from the outside of the tank and can be rotated through 180° to give a choice of either open on rise or close on rise switching configuration. Optional changeover switching can be specified.

Some customisation can be offered, for example, should internal tank fittings impede the operation of the switch, or if a different connection method is required.

Specifications:

T/LL12:

Body: Aluminium
 Float: Buna-N
 Thread: 1/2" BSP
 Electrical specification:
 Voltage: 240V
 Current: 0.5A
 Power: 10W
 Connection: Flying leads or DIN connector

T/LL17:

Body: Stainless steel
 Float: Buna-N
 Thread: 1/2" BSP
 Electrical specification:
 Voltage: 240V
 Current: 0.5A
 Power: 10W
 Connection: Flying leads or DIN connector



T/LL15:

Body: 316 stainless steel
 Float: Buna-N
 Thread: 1/2" BSP
 Electrical specification:
 Voltage: 240V
 Current: 0.5A
 Power: 10W
 Connection: Flying leads

T/LL19:

Body: Polypropylene
 Float: Polypropylene
 Thread: M16 X 2.0
 Electrical specification:
 Voltage: 240V
 Current: 0.5A
 Power: 10W
 Connection: Flying leads

