

S100 series temperature switches

The **S100 Series** of temperature switches comprises a wide range of switches each designed to meet a customer specific application. They are available in a selection of body styles, connector configurations, switching temperatures and senses, i.e. normally open, normally closed or changeover.

This range of products has been designed and engineered to be rugged and durable, and capable of extensive service in demanding environments. Suitable for use on many types of industrial engines, the **S100 Series** can withstand significant levels of vibration, shock, temperature and humidity.

Specification

Threads:

Standard thread sizes are 3/8"NPTF, 1/2"NPTF, 5/8"UNF, M14 or M18
Other thread sizes are also available.

Temperature ranges:


Standard N/O configuration (other ranges and switching senses are available upon request):

- 40 - 30°C
- 50 - 40°C
- 90 - 80°C
- 100 - 90°C
- 105 - 95°C

Environmental:

Service temperature: -40°C to +140°C
Vibration: 15.3 grms (3 orthoganol planes for 3 hours per plane) to BSEN 60068-2-64 : 1993

Examples of switch bodies, please enquire for other sizes.



2 WAY AMP JUNIOR TIMER CONNECTOR



Construction:

Body: Brass to CZ121/131
Connector: 30% PBT
Terminals: Brass CZ108 silver or nickel plated.

Electrical:

Switching current: 1 Amp max
Switching cycles: Min 100,000 operations

Connector types, please enquire for other designs

